AKEMI[®]

Printing date 27.03.2017	Version number 6	Revision: 27.03.2017
SECTION 1: Identification of the	substance/mixture and of the company/undertaking	3
• 1.1 Product identifier • Trade name:	Stain Repellent Nano Effect	
Article number: 1.2 Relevant identified uses of	11931, 11932/11933, 11934/11935, 11936, 11967	
the substance or mixture and uses advised against	No further relevant information available.	
<u>Application of the substance / the</u> mixture	Protective impregnation	
<u>1.3 Details of the supplier of the</u> <u>Manufacturer/Supplier:</u>	<u>safety data sheet</u> AKEMI chemisch technische Spezialfabrik GmbH Lechstrasse 28 D 90451 Nürnberg	Tel. +49(0)911-642960 Fax. +49(0)911-644456 e-mail info@akemi.de
Further information obtainable from:	Laboratory	
• <u>1.4 Emergency telephone</u> number:	Product Safety Department AKEMI chemisch technisc Tel. +49(0)911-64296-59 Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m. Friday from 07:30 a.m. to 13:30 p.m. +44 (171) 635 91 91 National Poison Inform. Centre Medical Toxicology Unit Avalonley Road London SE14 5ER	he Spezialfabrik GmbH
SECTION 2: Hazards identification	on	
2.1 Classification of the substance Classification according to Regulat GHS08 health hazard	ce or mixture	
Asp. Tox. 1 H304 May be fa	atal if swallowed and enters airways.	
Aquatic Chronic 4 H413 May caus • <u>Response:</u>	se long lasting harmful effects to aquatic life. IF SWALLOWED: Immediately call a POISON CENTE IF INHALED: Remove person to fresh air and keep co IF ON SKIN (or hair): Take off immediately all contam with water/shower. IF IN EYES: Rinse cautiously with water for several lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention Store in a well-ventilated place. Keep cool. Store locked up.	mfortable for breathing. iinated clothing. Rinse skin minutes. Remove contact n.
 <u>2.2 Label elements</u> Labelling according to Regulation (EC) No 1272/2008 Hazard pictograms 	The product is classified and labelled according to the	
	GHS08	
 <u>Signal word</u> Hazard-determining components 	Danger	
of labelling:	Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics	(Contd. on page 2)

according to 1907/2006/EC, Article 31

AKEMI®

Printing date 27.03.2017

Version number 6

Revision: 27.03.2017

Trade name: Stain Repellent Nano Effect

		(Contd. of page 1)
	Hydroca	bons, C11-C13, Isoalkanes, <2% aromatics
	Hydroca	bons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics
 Hazard statements 		y be fatal if swallowed and enters airways.
		y cause long lasting harmful effects to aquatic life.
Precautionary statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read label before use.
	P260	Do not breathe mist/vapours/spray.
	P280	Wear protective gloves.
	P301+P3	310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	P331	Do NOT induce vomiting.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local/regional/ national/international regulations.
 Additional information: 	EUH066	Repeated exposure may cause skin dryness or cracking.
· 2.3 Other hazards	The proc	luct does not contain any organic halogen compounds (AOX), nitrates,
	heavy m	etal compounds or formaldehydes.
 Results of PBT and vPvB asse 	ssment	
· PBT:	Not appli	cable.
· <u>vPvB:</u>	Not appli	cable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dooonption.		
 Dangerous components: 		
EC number: 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, Isoalkanes, <2% aromatics Asp. Tox. 1, H304 Aquatic Chronic 4, H413	25-50%
EC number: 920-901-0 Reg.nr.: 01-2119456810-40-xxxx	Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics	12.5-25%
EC number: 927-285-2 Reg.nr.: 01-2119480162-45	Hydrocarbons, C11-C14 isoalkanes, cycloalkanes, <2% aromatics	12.5-25%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	<10%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dowanol DPM substance with a Community workplace exposure limit	1-5%
CAS: 64741-65-7 EINECS: 265-067-2 Index number: 649-275-00-4 Reg.nr.: 01-2119472146-39	Naphtha (petroleum), heavy alkylate Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413	1-5%
 Additional information: 	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

 General information: 	Take affected persons out into the fresh air.	
	Position and transport stably in side position.	
	Immediately remove any clothing soiled by the product.	
 After inhalation: 	Supply fresh air; consult doctor in case of complaints.	
After skin contact:	If skin irritation continues, consult a doctor.	
	Immediately wash with water and soap and rinse thoroughly.	
		(0

according to 1907/2006/EC, Article 31

Printing date 27.03.2017

Version number 6

Revision: 27.03.2017

AKEMI[®]

GB

Trade name: Stain Repellent Nano Effect		
	(Contd. of page 2)	
· After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.	
 After swallowing: 	A person vomiting while laying on their back should be turned onto their side.	
 4.2 Most important symptoms 		
and effects, both acute and		
delayed	Headache	
	Dizziness	
	Dizziness	
	Nausea	
	Gastric or intestinal disorders	
Information for destan	Cramp	
Information for doctor:	Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)	
	a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal	
	dysfunction, state of excitement, coma. b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation,	
	cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.	
	Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air;	
	in case of peroral intake administration of Carbo medicinalis; only after	
	intubation conduct of gastrolavage in application of Carbo medicinalis; in case of	
	cramps administration of Diazepam 20 mg intravenously.	
· Hazards	Danger of impaired breathing.	
• 4.3 Indication of any immediate		
medical attention and special		
treatment needed	If swallowed or in case of vomiting, danger of entering the lungs.	
	If swallowed, gastric irrigation with added, activated carbon.	
	Monitor circulation.	
SECTION 5: Firefighting measures		
 5.1 Extinguishing media 		
 Suitable extinguishing agents: 	CO2, powder or water spray. Fight larger fires with water spray or alcohol	
	resistant foam.	
 5.2 Special hazards arising from 		
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.	
	Under certain fire conditions, traces of other toxic gases cannot be excluded,	
	e.g.:	
	Carbon monoxide (CO)	

• 5.3 Advice for firefighters

Protective equipment:
 Wear self-contained respiratory protective device.
 Do not inhale explosion gases or combustion gases.
 Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

<u>6.1 Personal precautions,</u> protective equipment and	
emergency procedures	Ensure adequate ventilation
	Use respiratory protective device against the effects of fumes/dust/aerosol. Keep away from ignition sources.
· 6.2 Environmental precautions:	Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water. (Contd. on page 4)

AKEMI®

according to 1907/2006/EC, Article 31 Printing date 27.03.2017 Version number 6 Revision: 27.03.2017 Trade name: Stain Repellent Nano Effect (Contd. of page 3) · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. See Section 7 for information on safe handling. · 6.4 Reference to other sections See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** · 7.1 Precautions for safe handling Keep receptacles tightly sealed. Store in cool, dry place in tightly closed receptacles. Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. · Information about fire - and explosion protection: Highly volatile, flammable constituents are released during processing. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground. Provide solvent resistant, sealed floor. Store only in the original receptacle. · Information about storage in one common storage facility: Store away from oxidising agents. Store away from foodstuffs. · Further information about storage Store receptacle in a well ventilated area. conditions: · 7.3 Specific end use(s) No further relevant information available. **SECTION 8: Exposure controls/personal protection** Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 123-86-4 n-butyl acetate WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm 34590-94-8 Dowanol DPM WEL Long-term value: 308 mg/m³, 50 ppm Sk · Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: Do not eat or drink while working. Apply solvent resistant skin cream before starting work. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Short term filter device: Respiratory protection: (Contd. on page 5) GB

Printing date 27.03.2017

Version number 6

Revision: 27.03.2017

AKEMI®

Trade name: Stain Repellent Nano Effect		
	(Contd. of page 4)	
 Protection of hands: 	Filter AX In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. After use of gloves apply skin-cleaning agents and skin cosmetics. Preventive skin protection by use of skin-protecting agents is recommended. After each cleaning use treatment creams, for very dry skin greasy ointments. Protective gloves	
	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Skin protection agent recommendation for preventive skin shelter without use of protective gloves:	
	STOKODERM (http://www.stoko.com) Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:	
	STOKO EMULSION (http://www.stoko.com) Skin protection recommendation for skin cleaning after product handling: FRAPANTOL (http://www.stoko.com) Skin protection agent recommendation for skin aftercare:	
	STOKO VITAN (http://www.stoko.com) The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.	
	This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).	
 Material of gloves 	Nitrile rubber, NBR Fluorocarbon rubber (Viton) Butyl rubber, BR	
	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.	
Penetration time of glove material	Value for the permeation: Level \leq 1, 30 min The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.	
• For the permanent contact gloves		
made of the following materials are suitable:	Nitrile rubber, NBR Camatril (KCL, Art_No. 730, 731, 732, 733) Fluorocarbon rubber (Viton)	
	Vitoject (KCL, Art_No. 890)	
	Butyl rubber, BR (Contd. on page 6)	

Printing date 27.03.2017

Version number 6

Revision: 27.03.2017

AKEMI®

Trade name: Stain Repellent Nano Effect			
 As protection from splashes gloves made of the following materials are 	Butoject (KCL, Art_No. 897, 898)	(Contd. of page 5)	
suitable:	Nitrile rubber, NBR Camatril (KCL, 730, 731, 732, 733)		
 Not suitable are gloves made of the following materials: 	Chloroprene rubber, CR Strong material gloves Leather gloves Natural rubber, NR		
Eye protection: Body protection:	Goggles recommended during refilling Solvent resistant protective clothing		
SECTION 9: Physical and chemic	al properties		
• <u>9.1 Information on basic physical</u> • General Information • <u>Appearance:</u> <u>Form:</u> <u>Colour:</u> • <u>Odour:</u>	and chemical properties Fluid Colourless Characteristic		
· pH-value:	Not applicable		
 <u>Change in condition</u> <u>Melting point/freezing point:</u> Initial boiling point and boiling ran 	Not applicable ge: 124 °C		
· <u>Flash point:</u>	62 °C		
· Flammability (solid, gas):	Not determined		
Ignition temperature:	370 °C		
<u>Auto-ignition temperature:</u>	Product is not selfigniting.		
Explosive properties:	Product does not present an explosion hazard.		
• <u>Explosion limits:</u> Lower: Upper:	3.0 Vol % 10.4 Vol %		
· <u>Vapour pressure at 20 °C:</u>	10.7 hPa		
· <u>Density at 20 °C:</u>	0.79 g/cm ³		
<u>Solubility in / Miscibility with</u> <u>water:</u>	Not miscible or difficult to mix.		
• <u>Viscosity:</u> <u>Dynamic:</u> <u>Kinematic at 20 °C:</u>	Not determined. 11 s (DIN 53211/4)		
<u>Solvent content:</u> <u>Organic solvents:</u>	93.8 %		
Solids content: • 9.2 Other information	3.1 % No further relevant information available.		

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

according to 1907/2006/EC, Article 31

Printing date 27.03.2017

Version number 6

Revision: 27.03.2017

AKEMI[®]

	(Contd. of page 6)
10.2 Chemical stability Thermal decomposition /	
conditions to be avoided:	No decomposition if used and stored according to specifications.
 10.3 Possibility of hazardous 	
reactions	Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
	Reacts with strong oxidising agents.
	Reacts with acids.
	Forms flammable gases/fumes.
 10.4 Conditions to avoid 	No further relevant information available.
 10.5 Incompatible materials: 	No further relevant information available.
10.6 Hazardous decomposition	
products:	Carbon monoxide and carbon dioxide Hydrogen fluoride

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

<u>Acute toxicity</u>	Based on available data, the classification criteria are not met.
 LD/LC50 values relevant for 	classification:
ATE (Associal Teachelites Estima	- ()

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 333 mg/l (rat)

Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics

nyulocarbons, CTT-CTS, Isoaikanes, <2% aromatics				
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>5000 mg/kg (rabbit)		
 Primary irr 	itant effect	t:		
· Skin corro	sion/irritati	on	Based on available data, the classification criteria are not met.	
 Serious eye damage/irritation 		/irritation	Based on available data, the classification criteria are not met.	
 Respiratory or skin sensitisation 		ensitisation	Based on available data, the classification criteria are not met.	
 CMR effect 	cts (carcino	ogenity, mutag	genicity and toxicity for reproduction)	
 Germ cell 	mutagenic	ity	Based on available data, the classification criteria are not met.	
Carcinogenicity			Based on available data, the classification criteria are not met.	
 Reproductive toxicity 			Based on available data, the classification criteria are not met.	
 STOT-single exposure 		re	Based on available data, the classification criteria are not met.	
 STOT-repeated exposure 		osure	Based on available data, the classification criteria are not met.	
Aspiration hazard			May be fatal if swallowed and enters airways.	

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:				
Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics				
EC50/48h >1000 mg/l (daphnia magna)				
EC50/72h >1000 mg/l (green alge)				
12.2 Persistence and				
degradability	No further relevant information available.			
 Other information: 	The product is not easily biodegradable.			
· 12.3 Bioaccumulative potential	No further relevant information available.			
· 12.4 Mobility in soil	No further relevant information available.			
 Additional ecological information: 				
General notes:	Do not allow product to reach ground water, water course or sewage system.			
	Water hazard class 1 (German Regulation) (Self-assessment): slightly			
	hazardous for water			
 12.5 Results of PBT and vPvB assessment 				
· PBT:	Not applicable.			
	(Contra on none 0)			

Printing date 27.03.2017

Trade name: Stain Repellent Nano Effect

Version number 6

Revision: 27.03.2017

AKEMI®

		(Contd. of page	7)		
$\cdot \underline{vPvB}$	n a duana a affa ata	Not applicable.			
• <u>12.6 Othe</u>	r adverse effects	No further relevant information available.			
SECTION	SECTION 13: Disposal considerations				
	te treatment methods				
· <u>Recomme</u>	endation	Must not be disposed together with household garbage. Do not allow product to reach sewage system.			
 European 	waste catalogue				
20 00 00		6 (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND TES) INCLUDING SEPARATELY COLLECTED FRACTIONS			
20 01 00	separately collected fra-	ctions (except 15 01)			
20 01 13*	solvents				
07 00 00	WASTES FROM ORGA	ANIC CHEMICAL PROCESSES			
07 07 00	wastes from the MFSU	of fine chemicals and chemical products not otherwise specified			
07 07 04*	other organic solvents,	washing liquids and mother liquors			
· Uncleaned	d packaging:		_		
· <u>Recomme</u>		Empty contaminated packagings thoroughly. They may be recycled after	er		
	· · · ·	thorough and proper cleaning.			
 Recomme 	ended cleansing agents:	Alcohol			
SECTION	14: Transport information	tion			
· 14.1 UN-N	lumber		٦		
$\cdot \overline{ADR}, ADR$	N, IMDG, IATA	Void			
• 14.2 UN p • ADR, ADN	roper shipping name N, IMDG, IATA	Void			
· 14.3 Tran	sport hazard class(es)				
	N, IMDG, IATA				
· <u>Class</u>		Void			
· 14.4 Pack · <u>ADR, IMD</u>		Void			
· 14.5 Envi · Marine po	ronmental hazards: llutant:	No			
	ial precautions for use		-		
	•		-		
Marpol ar	sport in bulk according nd the IBC Code	Not applicable.			
 Transport 	nsport/Additional information: Not dangerous according to the above specifications.				
· <u>UN</u> "Mode	el Regulation":	Void			
SECTION 15: Regulatory information • <u>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</u> • <u>Directive 2012/18/EU</u> • <u>Named dangerous substances -</u> <u>ANNEX I</u> • <u>REGULATION (EC) No 1907/2006</u> • Canditings of pastriction: 2					
ANNEX X	VII	Conditions of restriction: 3 (Contd. on page	9)		
		Genita. on page	э) ;В		



GB

according to 1907/2006/EC, Article 31					
Printing date 27.03.2017	Version number 6	Revision: 27.03.2017			
Trade name: Stain Repellent Nano Effect					
		(Contd. of page 8)			
National regulations:					
 Information about limitation of use: 	Employment restrictions concerning juveniles must Employment restrictions concerning pregnant observed.				
Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazard class 1 (Self-assessment): slig		hazardous for water.			
 <u>15.2 Chemical safety</u> assessment: 	A Chemical Safety Assessment has not been car	ried out.			
SECTION 16: Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.					
• <u>Relevant phrases</u>	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airway H336 May cause drowsiness or dizziness. H413 May cause long lasting harmful effects to ad				
<u>Recommended restriction of use</u>	refer to Technical Data Sheet (TDS)				
 Department issuing SDS: Contact: Abbreviations and acronyms: 	Laboratory Dieter Zimmermann RID: Règlement international concernant le transport des man fer (Regulations Concerning the International Transport of Dan ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandise Agreement concerning the International Carriage of Dangerou IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labe EINECS: European Inventory of Existing Commercial Chemica ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Cl LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – 4 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - lor	ngerous Goods by Rail) s dangereuses par Route (European is Goods by Road) Illing of Chemicals al Substances hemical Society) Category 3			
 * Data compared to the previous version altered. 	Adaptation in accordance with REACH directive 1				
International Product Registration Status	USA (Toxic Substances Control Act, TSCA) J (Existing and New Chemical Substance List, EN				