

Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 1 / 12

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification				
1.1. Product identifier				
Product name	PROSEAL NA	ANO		
1.2. Relevant identified uses of the substance or m	xture and use	s advised agai	nst	
Intended use	Protective for	r stones		
Identified Uses	Industrial		Professional	Consumer
ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR	\checkmark		 Image: A start of the start of	-
1.3. Details of the supplier of the safety data sheet				
Name Full address District and Country e-mail address of the competent person	Tenax Spa Via I Maggio, 37020 Tel. Fax	226 Volargne Italy +39 045 6887 +39 045 68624		(VR)
responsible for the Safety Data Sheet	msds@tenax	.it		
Supplier:		831173 - Fax 0	enter Drive Suite 400 01 7045833166), 28273 Charlotte NC, US
1.4. Emergency telephone number				
For urgent inquiries refer to	Infotrac US and Cana Int'l: 1-352-32 info@infotrac		5053	

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement Flammable liquid, category 2 Eye irritation, category 2 Specific target organ toxicity - single exposure, category 3 Hazard pictograms:



Signal words:

H336

Danger

Hazard statements: H225 H319

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 2 / 12

2. Hazards identification

Precautionary	statements:						
Prevention:							
P210	Keep av	vay from heat,	hot surfaces, sparks, open flames and other ignition sources. No smoking.				
P261		Avoid breathing dust / fume / gas / mist / vapours / spray. Use only non-sparking tools.					
P242 P280		Wear protective gloves / eye protection / face protection.					
P271		Use only outdoors or in a well-ventilated area.					
P264		Wash the hands thoroughly after handling.					
P240		Ground / bond container and receiving equipment.					
P243		Take precautionary measures against static discharge.					
P241	Use exp	losion-proof el	ectrical / ventilating / lighting / / equipment.				
Response:							
P305+P351		IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.					
P303+P361	+P353 IF ON S	KIN (or hair): T	ake off immediately all contaminated clothing. Rinse skin with water / shower.				
P312			R / doctor / / if you feel unwell.				
P337+P313			Get medical advice / attention.				
P304+P340			erson to fresh air and keep comfortable for breathing.				
P370+P378	In case	of fire: use CO	2, sand, powder to extinguish.				
Storage: P403+P235	Storo in	a woll vontilate	nd nlaco. Koon cool				
P403+P233			ed place. Keep cool. ed place. Keep container tightly closed.				
P405		cked up.					
Disposal:							
P501	Dispose	of contents / c	ontainer according to applicable law.				
2.2. Other hazaro Additional haza Repeated e		skin drvness or	cracking.				
-		-					
		n on ingra	diante				
	ion/informatio	n on ingre	dients				
3.2. Mixtures	Ion/Informatio	<mark>n on ingre</mark>	dients				
3.2. Mixtures Contains:							
3.2. Mixtures Contains: Identification	x = Conc		classification:				
3.2. Mixtures Contains: Identification N-BUTYL ACE	x = Conc	. %	Classification:				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS	x = Conc TATE 123-86-4						
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC	x = Conc TATE 123-86-4 204-658-1	. %	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX	x = Conc TATE 123-86-4 204-658-1 607-025-00-1	.% 49≤x< 51	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg.	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29	.% 49≤x< 51	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE	.% 49≤x< 51	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg.	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29	.% 49≤x< 51	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE	.% 49≤x< 51	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5	.% 49≤x< 51 45≤x< 47	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg.	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4	.% 49≤x< 51 45≤x< 47	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg. Ethyl lactate	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5 01-2119475103-46	.% 49≤x< 51 45≤x< 47	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg.	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5	.% 49≤x< 51 45≤x< 47	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 3 H226, Serious eye damage, category 1 H318,				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg. Ethyl lactate CAS	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5 01-2119475103-46 97-64-3	.% 49≤x< 51 45≤x< 47	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg. Ethyl lactate CAS EC	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5 01-2119475103-46	.% 49≤x< 51 45≤x< 47	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 3 H226, Serious eye damage, category 1 H318,				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg. Ethyl lactate CAS	x = Conc TATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5 01-2119475103-46 97-64-3 202-598-0	.% 49≤x< 51 45≤x< 47 2.5≤x< 3	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 3 H226, Serious eye damage, category 1 H318,				
3.2. Mixtures Contains: Identification N-BUTYL ACE CAS EC INDEX REACH Reg. ETHYL ACETA CAS EC INDEX REACH Reg. Ethyl lactate CAS EC INDEX REACH Reg.	x = Conc ETATE 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 ATE 141-78-6 205-500-4 607-022-00-5 01-2119475103-46 97-64-3 202-598-0 607-129-00-7	.% 49≤x< 51 45≤x< 47 2.5≤x< 3	Classification: Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336 Flammable liquid, category 3 H226, Serious eye damage, category 1 H318,				

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again. INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 3 / 12

4. First-aid measures

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 4 / 12

'. Handling and storage ... /

stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA USA	NIOSH-REL OSHA-PEL	NIOSH publication No. 2005-149, 3th printing, 2007. Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2020

				N-DOT I		
Threshold Limit	Value					
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	241	50	723	150	
TLV-ACGIH	-		50		150	
OSHA	USA	710	150			
CAL/OSHA	USA	710	150	950	200	
NIOSH	USA	710	150	950	200	

				ETHYL	ACETATE	
Threshold Limit	Value					
Туре	Country	TWA/8h		STEL/15	min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	1441	400			
OEL	EU	734	200	1468	400	
OSHA	USA	1400	400			
CAL/OSHA	USA	1.4	400			
NIOSH	USA	1400	400			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations. HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence



Exposure controls/personal protection ...

of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

HAND PROTECTION: Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time> 480 minutes. Material thickness:

NITRILE short contact> 0.38 mm prolonged contact> 0.55 mm FLUOROELASTOMER short contact> 0.50 mm prolonged contact> 1.50 mm

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance Colour Odour Odour threshold pH		Value liquid colourless characteristic Not available Not available			Information Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent
					mixture)
Melting point / freezing point		Not available			
Initial boiling point	>		(95 °F)		
Boiling range		Not available			
Flash point	<	23 °C Not available		(73,4 °F)	
Evaporation rate					
Flammability (solid, gas)		Not available Not available			
Lower inflammability limit Upper inflammability limit		Not available			
Lower explosive limit		Not available			
Upper explosive limit		Not available			
Vapour pressure		Not available			
Vapour pressure Vapour density		Not available			
Relative density		0.85 g/cm3			
Solubility		insoluble in water	r		
Partition coefficient: n-octanol/water		Not available	•		
Auto-ignition temperature		Not available			
Decomposition temperature		Not available			
Viscosity		Not available			
Explosive properties		Not available			
Oxidising properties		Not available			
9.2. Other information					
VOC :		94,00 % - 799	9,00	g/litre	

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

N-BUTYL ACETATE

Decomposes on contact with: water.



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 6 / 12

10. Stability and reactivity ... / >

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising

agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames. ETHYL ACETATE Avoid exposure to: light,sources of heat,naked flames.

10.5. Incompatible materials

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

ETHYL ACETATE

Incompatible with: acids,bases,strong oxidants,aluminium,nitrates,chlorosulphuric acid.Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Ethyl lactate LD50 (Oral): LC50 (Inhalation mists/powders):

ETHYL ACETATE LD50 (Oral): LD50 (Dermal): LC50 (Inhalation vapours):

N-BUTYL ACETATE

> 2000 mg/kg > 5.4 mg/l/4h Ratto

5620 mg/kg ratto > 20000 mg/kg coniglio > 6000 ppm/4h ratto



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 7 / 12

11. Toxicological information ... / >

LD50 (Oral): LD50 (Dermal): LC50 (Inhalation vapours): > 6400 mg/kg Rat> 5000 mg/kg Rabbit21.1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Ethyl lactate	
LC50 - for Fish	320 mg/l/96h Danio rerio
EC50 - for Crustacea	683 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	2300 mg/l/72h Pseudokirchneriella subcapitata
ETHYL ACETATE	
LC50 - for Fish	230 mg/l/96h pimephales promelas
EC50 - for Crustacea	165 mg/l/48h daphnia

12.2. Persistence and degradability



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 8 / 12

12. Ecological information ... / >

ETHYL ACETATE		
Solubility in water Rapidly degradable	> 10000 mg/l	
N-BUTYL ACETATE		
Solubility in water	1000 - 10000 mg/l	
12.3. Bioaccumulative potential		
ETHYL ACETATE		
Partition coefficient: n-octanol/water	0.68	
BCF	30	
N-BUTYL ACETATE		
Partition coefficient: n-octanol/water	2.3	
BCF	15.3	
12.4. Mobility in soil		
N-BUTYL ACETATE		
Partition coefficient: soil/water	< 3	
12.5. Results of PBT and vPvB assessment		
On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.		

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1993

14.2. UN proper shipping name

ADR / RID:	FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; N-BUTYL ACETATE)
IMDG:	FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; N-BUTYL ACETATE)
IATA:	FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; N-BUTYL ACETATE)



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 9 / 12

14. Transport information ... / >:

14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3
IATA:	Class: 3	Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:

IMDG:

IATA:

HIN - Kemler: 33 Special provision: 274, 601, 640D EMS: F-E, <u>S-E</u> Cargo: Pass.: Special provision:

Limited Quantities: 1 L

Limited Quantities: 1 L Maximum quantity: 60 L Maximum quantity: 5 L A3 Tunnel restriction code: (D/E)

Packaging instructions: 364 Packaging instructions: 353

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b): No component(s) listed.

Clean Air Act Section 602 Class I Substances: No component(s) listed.

Clean Air Act Section 602 Class II Substances: No component(s) listed.

Clean Water Act – Priority Pollutants: No component(s) listed.

Clean Water Act – Toxic Pollutants: No component(s) listed.

DEA List I Chemicals (Precursor Chemicals): No component(s) listed.



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 10 / 12

15. Regulatory information

DEA List II Chemicals (Essential Chemicals): No component(s) listed.

EPA List of Lists: 313 Category Code: No component(s) listed.

EPCRA 302 EHS TPQ: No component(s) listed.

EPCRA 304 EHS RQ: No component(s) listed.

CERCLA RQ:

123-86-4 N-BUTYL ACETATE 141-78-6 ETHYL ACETATE

EPCRA 313 TRI: No component(s) listed.

RCRA Code: 141-78-6

ETHYL ACETATE

CAA 112 (r) RMP TQ: No component(s) listed.

State Regulations

Massachussetts:	
123-86-4	N-BUTYL ACETATE
141-78-6	ETHYL ACETATE
97-64-3	Ethyl lactate

Minnesota: 123

123-86-4	N-BUTYL ACETATE
141-78-6	ETHYL ACETATE

New Jersey: 123-86

w Jeisey.	
123-86-4	N-BUTYL ACETATE
141-78-6	ETHYL ACETATE
97-64-3	Ethyl lactate

New York: 123-86-4

9

N-BUTYL ACETATE
ETHYL ACETATE

Pennsylvania:

123-86-4	N-BUTYL ACETATE
141-78-6	ETHYL ACETATE
97-64-3	Ethyl lactate

California: 123-86-4

123-86-4	N-BUTYL ACETATE
141-78-6	ETHYL ACETATE

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention: None



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 11 / 12

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597 - Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".



Revision nr.1 Dated 11/4/2021 First compilation Printed on 11/4/2021 Page n. 12 / 12

16. Other information ... / >

- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.